



Light Soda-Ash

Description:

White, powder, hygroscopic, easily dissolved in water, clear and colorless in water solution material. Main compound is Sodium Carbonate.

Standard No: TS 525 TYPE 3B

Chemical Specifications:

Sodium Carbonate, (Na ₂ CO ₃) (%)	99.10 min.
Sodium Chloride, (NaCl) (%)	0.25 max.
Iron, (Fe) (ppm)	15 max.
Insoluble matter in water (%)	0.01 max.
Sulfate, SO ₄ ²⁻ (%)	0,027 max.

Physical Specifications:

Structure of the Material: Free flowing powder
Standard density : 0.47 - 0,59 gr/cm³

Packaging:

- In block-bottom laminated polypropylene (PP) bags of 25 or 40 kgs. each
- Palletized and shrink-wrapped 1000 kg. each, containing 25 kg. laminated block-bottom PP bags.
- In polypropylene big-bags with polyethylene (PE) in-liner and four loops, 650 or 1000 kgs. each
- In bulk

Control:

According to TS 525 and Soda Sanayii A.Ş. Soda Plant LIGHT SODA ASH Control (analysis) Instruction.

Uses:

Glass, detergent, textile, chemical, paper industries and production of other sodium compounds.



Determined specifications of our products is valid for conditions under our control.
Please refer to Material Safety Data Sheet of Light Soda for handling, storage and end use.



ŞİŞECAM

ŞİŞECAM is an establishment of TÜRKİYE İŞ BANKASI.

Marketing and Sales: ŞİŞECAM CHEMICALS GROUP

İş Kuleleri Kule-3, Kat:16 34330 / 4. Levent - İstanbul Turkey Tel: +90 212 350 35 75 - 78
Fax: +90 212 350 45 75 - 78 Web: www.sisecam.com / www.sodakrom.com